



ATc

5" BASE

|     |     |               |
|-----|-----|---------------|
| SKU | RoW | CGAX019603103 |
| SKU | US  | CGAX019603120 |

| Ser                             | Nomenclature/Description                                                | Specification ATC                                                                                                           |                        |                        |
|---------------------------------|-------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|------------------------|------------------------|
| Part-1: General specification   |                                                                         |                                                                                                                             |                        |                        |
| 1.                              | Nomenclature                                                            | 9 mm Semi Auto Pistol                                                                                                       |                        |                        |
| 2.                              | Year of production                                                      | 2025                                                                                                                        |                        |                        |
| 3.                              | Model                                                                   | STEYR ATc 5"                                                                                                                |                        |                        |
| 4.                              | Name of the manufacturer                                                | STEYR ARMS d.o.o.                                                                                                           |                        |                        |
| 5.                              | Country of origin                                                       | Slovenia/Austria                                                                                                            |                        |                        |
| 6.                              | Product compliant                                                       | to NATO and C.I.P. standards                                                                                                |                        |                        |
| Part-2: Technical specification |                                                                         |                                                                                                                             |                        |                        |
| 7.                              | Caliber                                                                 | 9x19 mm                                                                                                                     |                        |                        |
| 8.                              | Magazine capacity                                                       | 18/20                                                                                                                       |                        |                        |
| 9.                              | Number of magazines per weapon                                          | Two or according to requirement                                                                                             |                        |                        |
| 10.                             | Magazines have indication holes                                         | YES                                                                                                                         |                        |                        |
| 11.                             | Operation mechanism                                                     | Browning short recoil-operated, locked-breech, semi-auto                                                                    |                        |                        |
| 12.                             | Weight & Dimension of pistol                                            |                                                                                                                             |                        |                        |
| a.                              | Weight without magazine with M grip (+/-15g)                            | 1141g                                                                                                                       |                        |                        |
| b.                              | Weight with empty magazine (+/-15g)                                     | Polymer 18RD 1228g                                                                                                          | Polymer 18RD+2RD 1238g | Aluminium 18+2RD 1245g |
| c.                              | Weight with full magazine (+/-15g)                                      | Polymer 18RD 1450g                                                                                                          | Polymer 18RD+2RD 1484g | Aluminium 18+2RD 1490g |
| d.                              | Magazine empty weight: Grips:                                           | Polymer 18RD-87g; Polymer 18+2RD-98g; Aluminium 18+2RD-104g<br>S-N/A; M-48g; L-N/A                                          |                        |                        |
| e.                              | Length of pistol                                                        | 216mm                                                                                                                       |                        |                        |
| f.                              | Barrel length                                                           | 127mm                                                                                                                       |                        |                        |
| g.                              | Barrel profile:                                                         |                                                                                                                             |                        |                        |
| (1)                             | Twist direction                                                         | 1:10' / 250mm; RH                                                                                                           |                        |                        |
| (2)                             | Number of surface (grooves)                                             | 6                                                                                                                           |                        |                        |
| h.                              | Height including optional magazine (possible delivery scope) and sights | Normal sight<br>Polymer floorplate 18RD - 143mm<br>Polymer floorplate 18+2RD - 156mm<br>Aluminium floorplate 18+2RD - 150mm |                        |                        |
| i.                              | Height excluding magazine and with sights                               | 142mm                                                                                                                       |                        |                        |
| j.                              | Height excluding magazine and without sights                            | 139mm                                                                                                                       |                        |                        |
| k.                              | Width                                                                   | Overall: 43mm; Slide: 26mm                                                                                                  |                        |                        |
| l.                              | Sight radius                                                            | 180 mm from the front sides of sights                                                                                       |                        |                        |
| 13.                             | Muzzle velocity                                                         | S&B FMJ 124gr (Vo=*360m/s) *depends of ammunition                                                                           |                        |                        |
| 14.                             | Muzzle energy                                                           | S&B FMJ 124gr (E=*512J) *depends of ammunition                                                                              |                        |                        |
| 15.                             | Maximum range                                                           | S&B FMJ 124gr (*100m) *depends of ammunition                                                                                |                        |                        |
| 16.                             | Effective range                                                         | 50m                                                                                                                         |                        |                        |
| 17.                             | Accuracy with standard ammunition (by testing machine)                  | At 25m: 50mm + caliber diameter                                                                                             |                        |                        |
| 18.                             | Trigger travel for discharge                                            | 2,5mm                                                                                                                       |                        |                        |
| 19.                             | Trigger reset                                                           | Adjustable                                                                                                                  |                        |                        |
| 20.                             | Safety system                                                           | Ambidextrous manual safety + Firing pin safety +Drop safety                                                                 |                        |                        |
| 21.                             | Picatinny rail                                                          | MIL SPEC Standard 1913                                                                                                      |                        |                        |
| 22.                             | Button for slide release                                                | Left - Overall width 31mm                                                                                                   |                        |                        |
| 23.                             | Button for magazine release (Ambidextrous)                              | Normal - Overall width 32mm                                                                                                 |                        |                        |



STEYR ARMS  
WEB



STEYR ARMS AT  
PISTOL SERIES



STEYR ARMS AT  
PICTURE WORLD





**ATC**

5" BASE

|                                                                              |                                                                                                  |                                                                                                                             |
|------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| 24.                                                                          | Manual safety (Ambidextrous)                                                                     | YES                                                                                                                         |
| 25.                                                                          | Interchangeable grips                                                                            | YES (3 sizes available)                                                                                                     |
| 26.                                                                          | Rear sight                                                                                       | Adjustable LPA sight or according to customer request                                                                       |
| 27.                                                                          | Front sight                                                                                      | Iron drift adjustable with white dot (fiber optic, night inserts – optional) or according to customer request               |
| 28.                                                                          | OR plates                                                                                        | YES                                                                                                                         |
| 29.                                                                          | Loading status indicator                                                                         | NO                                                                                                                          |
| 30.                                                                          | Trigger action                                                                                   | DA/SA                                                                                                                       |
| 31.                                                                          | Trigger force                                                                                    | SA:17N ± 3N; DA:42N ±3N                                                                                                     |
| 32.                                                                          | Frame material                                                                                   | Stainless steel                                                                                                             |
| 33.                                                                          | Slide material                                                                                   | Stainless steel                                                                                                             |
| 34.                                                                          | Barrel material                                                                                  | Cold forged Chromalloy steel – nitrocarburizing surface protection                                                          |
| 35.                                                                          | Disassembly pistol                                                                               | Disassembly the slide by pushing out and rotating disassembly lever clockwise, then slide the slide forward from the frame. |
| 36.                                                                          | Cocking firing indicator                                                                         | YES                                                                                                                         |
| 37.                                                                          | Combat rate of fire                                                                              | /                                                                                                                           |
| 38.                                                                          | Cartridge                                                                                        | 9x19mm parabellum                                                                                                           |
| 39.                                                                          | Type of ammo that can be fired by this pistol along with the weight, length and other dimensions | 9x19 mm SAAMI and CIP approved ammunition                                                                                   |
| 40.                                                                          | Feed                                                                                             | Self-loading                                                                                                                |
| 41.                                                                          | Rifling                                                                                          | Twist 1:10' / 250mm; Grooves 6, RH                                                                                          |
| 42.                                                                          | Service life                                                                                     | 50.000 rd (40.000 shots + 10.000 dry shots)                                                                                 |
| 43.                                                                          | Warranty                                                                                         | 10 years (with replacement of spare parts based on maintenance guidelines)                                                  |
| 44.                                                                          | Reliability                                                                                      | 2 jam per 1.501 – 2.500rd                                                                                                   |
| 45.                                                                          | Model validity                                                                                   | Minimum 15 years from signing of contract                                                                                   |
| 46.                                                                          | Color options                                                                                    | Black / Silver / optional                                                                                                   |
| 47.                                                                          | <b><u>Operating/Storage condition</u></b>                                                        |                                                                                                                             |
|                                                                              | a. Operating temperature range                                                                   | -60°C / + 60°C                                                                                                              |
|                                                                              | b. Storage temperature range                                                                     | -30°C / + 60°C                                                                                                              |
|                                                                              | c. Humidity permissible condition for operation                                                  | 100%                                                                                                                        |
|                                                                              | d. Maximum permissible humidity condition for storage                                            | Up to 90% with proper cleaning and lubrication                                                                              |
|                                                                              | e. Operation during fog, rain and snow                                                           | YES                                                                                                                         |
| <b><u>Part-3: Testing requirements</u></b>                                   |                                                                                                  |                                                                                                                             |
| 48.                                                                          | Standard STANAG 4512 – D/14 NATO small arms test manual                                          | YES                                                                                                                         |
| <b><u>Part-4: NATO stock number</u></b>                                      |                                                                                                  |                                                                                                                             |
| 49.                                                                          | NSN                                                                                              | -                                                                                                                           |
| <b><u>Part-5: Training requirement</u></b>                                   |                                                                                                  |                                                                                                                             |
| <b><u>Part-5A: User training</u></b>                                         |                                                                                                  |                                                                                                                             |
| 50.                                                                          | User training                                                                                    | YES                                                                                                                         |
| <b><u>Part-5B: Operation, repair and maintenance training</u></b>            |                                                                                                  |                                                                                                                             |
| 51.                                                                          | Operation, repair and maintenance training                                                       | YES                                                                                                                         |
| <b><u>Part-5C: Equipment and management training</u></b>                     |                                                                                                  |                                                                                                                             |
| 52.                                                                          | Equipment and management training                                                                | YES                                                                                                                         |
| <b><u>Part-6: Repair and maintenance requirement less list of spares</u></b> |                                                                                                  |                                                                                                                             |
| 53.                                                                          | a. SST/Measuring & testing set                                                                   | YES                                                                                                                         |
|                                                                              | b. SSM                                                                                           | To be provided                                                                                                              |
|                                                                              | c. Books & publications                                                                          | To be provided                                                                                                              |
| <b><u>Part-7: List of spares</u></b>                                         |                                                                                                  |                                                                                                                             |
| 54.                                                                          | List of spares                                                                                   | YES                                                                                                                         |
| <b><u>Part-8: Other accessories</u></b>                                      |                                                                                                  |                                                                                                                             |
| 55.                                                                          | Other accessories                                                                                | To be provided                                                                                                              |

This document and the information either contained in it or disclosed by it are the property of STEYR ARMS d.o.o. and are issued in strict confidence. All design, manufacture, use, reproduction, and sale rights are reserved by STEYR ARMS d.o.o. These rights can only be waived with the prior formal consent of STEYR ARMS d.o.o. Report should only be reproduced in full and with the approval of STEYR ARMS d.o.o.

STEYR ARMS  
WEBSTEYR ARMS AT  
PISTOLSERIESSTEYR ARMS AT  
PICTUREWORLD